

Power System Module

Accessories

Mounting kit

for PSM busbars

Without cable routing

For		Model No.
TS	For static installation	7856.011
TS-IT	Plug and play compatibility system	7856.029

With cable routing

For		Model No.
TS	For static installation	7856.022
	Adjustable, for freely accessible 482.6 mm (19") level	7856.023



Connection cable

for PSM-busbar

Connection cable, 3-phase			
	Length m	Packs of	Model No.
CEE-conforming 5-pole/16 A	3	1 pc(s).	7856.025
Connection cable, single-phase			
CEE-conforming 3-pole/16 A	3	1 pc(s).	7856.026
Connection cable, UPS, single-phase			
C14/X-Com 10 A/PMC 12, 1 – 2 kVA	3	1 pc(s).	7856.027
C20/X-Com 16 A/PMC 12, 3 kVA	3	1 pc(s).	7856.030
Connection cable C19/C20			
16 A	2	1 pc(s).	7200.217
Connection cable C13/C14			
16 A	0.5	2 pc(s).	7856.014



Cable lock PSM

for all modules with EN 60 320 C13 connector configurations


All terminal connection cables are therefore protected against unintentional disconnection of the power supply. Two bars are needed for two cables.

Version	Packs of	Model No.
Bar	20 pc(s).	7856.013



Accessories:

- Optimum locking function is only available with connection cable 7856.014, see page 413



Overvoltage protection PSM

Connected upstream of the busbar.

- Fine fuse
- Connection:
 - Socket Wago X-COM
 - Connector Wago X-COM

Overvoltage protection	Packs of	Model No.
With adaptor connector	1 pc(s).	7856.170

Note:

- One overvoltage protection is required for each infeed

